



GRADE 80 & 100 CHAIN SLINGS

Chain slings are the classic and widely used load handling attachment for a wide variety of lifting applications. They feature flexibility and extremely high durability.

Premium quality chain slings assembled with Thiele chain made in Germany.

We offer complete chain slings and components in grades 80 & 100 as well as corresponding accessories and spare parts. Chain slings made to order according to your requirements.

All lifting components are uniformly marked with equivalent chain size and grade.

Safety factor: 4:1

WORKING LOAD LIMITS 120 One Two Leg **Three Leg** Four Leg Leg Angle from vertical - β 30° 30° Angle between legs - α 60° 60° 90° 90° Chain Dia. Grade (mm 3.90 80 1.50 2.55 2.10 1.50 3.90 3.15 2.25 3.15 2.25 8 100 2.50 4.25 3.50 2.50 6.50 5.25 3.75 6.50 5.25 3.75 80 3.15 5.35 4.41 3.15 8.19 6.62 4.72 8.19 6.62 4.72 100 4.00 6.80 10 5.60 4.00 10.40 8.40 6.00 10.40 8.40 6.00 13 80 5.30 9.00 7.42 5.30 13.78 11.13 7.95 13.78 11.13 7.95 13 100 9.38 10.05 6.70 11.39 6.70 17.42 14.07 17.42 14.07 10.05 16 80 8.00 13.60 11.20 8.00 20.80 16.80 12.00 20.80 16.80 12.00 16 100 10.00 17.00 14.00 10.00 26.00 21.00 15.00 26.00 21.00 15.00 20 12.50 21.25 80 17.50 12.50 32.50 26.25 18.75 32.50 26.25 18.75 39.00 31.50 39.00 31.50 22.50 26 20.40 34.68 28.56 20.40 53.00 42.84 30.60 53.00 42.84 30.60 32 31.50 53.55 44.10 31.50 81.90 66.15 47.25 81.90 66.15 Factor 1.0 1.7 1.0 2.6 2.1 1.5 2.6 2.1 1.5 1.4

1 LEG SLING

(Grade 80 Shown)







3 LEG SLING

(Grade 80 Shown)



4 LEG SLING

(Grade 100 Shown)



Assembled with chain from:







Made in Germany





GRADE 80 & 100 CHAIN SLINGS

Chain slings are the classic and widely used load handling attachment for a wide variety of lifting applications. They feature flexibility and extremely high durability.

STANDARD SLINGS



(Grade 80 Shown)













(Grade 100 Shown)



OTHER SLING EXAMPLES

CHOKER SLING

(Grade 100 Shown)



ENDLESS SLING

(Grade 80 Shown)



SINGLE ADJUSTABLE LOOP CHAIN SLING

(Grade 100 Shown)



SINGLE BASKET SLING

(Grade 80 Shown)



DOUBLE BASKET SLING

(Grade 100 Shown)



Assembled with chain from:







Made in Germany





GRADE 80 CHAIN SLINGS

Chain slings are the classic and widely used load handling attachment for a wide variety of lifting applications. They feature flexibility and extremely high durability.

Premium quality chain slings assembled with Thiele chain made in Germany to EN818-2.

We offer complete chain slings and components as well as corresponding accessories and spare parts.

Chain slings made to order according to your requirements.

All lifting components are uniformly marked with equivalent chain size and grade.

Safety factor: 4:1


WORKING LOAD LIMITS 120 One Two Leg **Three Leg** Four Leg Leg Angle from vertical - β 30° Angle between legs - α 60° 60° 90° 90° Chain Dia. (mm) 7 1.50 2.55 2.10 1.50 3.90 3.15 2.25 3.90 3.15 2.25 10 4.41 3.15 5.35 6.62 4.72 8.19 6.62 3.15 8.19 4.72 13 5.30 9.00 7.42 5.30 13.78 11.13 7.95 13.78 11.13 7.95 16 13.60 11.20 8.00 20.80 16.80 12.00 8.00 20.80 16.80 12.00 20 12.50 21.25 17.50 12.50 32.50 26.25 32.50 26.25 18.75 15.00 25.50 39.00 22.50 39.00 22.50 21.00 15.00 31.50 31.50 26 20.40 34.68 28.56 20.40 53.00 42.84 30.60 53.00 42.84 30.60 32 31.50 53.55 44.10 31.50 81.90 66.15 47.25 81.90 66.15 47.25 **Factor** 1.0 1.7 2.6 2.1 2.6 1.5 1.4 1.0 1.5 2.1

If Grade 80 - Alloy slings are used at temperatures exceeding 200°C, then the Working Load Limit has to be reduced.

-40 to +200°C 100% +200 to +300°C 90% +300 to +400°C 75% 1 LEG SLING

2 LEG SLING





3 LEG SLING



4 LEG SLING



Assembled with chain from:











GRADE 100 CHAIN SLINGS

Chain slings are the classic and widely used load handling attachment for a wide variety of lifting applications. They feature flexibility and extremely high durability.

Premium quality chain slings assembled with Thiele chain made in Germany to ASTM973.

We offer complete chain slings and components as well as corresponding accessories and spare parts.

Chain slings made to order according to your requirements.

All lifting components are uniformly marked with equivalent chain size and grade.

Safety factor: 4:1

25% stronger than the corresponding diameter Grade 80 chain.

WORKING LOAD LIMITS One Two Leg **Three Leg Four Leg** Leg Angle from vertical - β 30° Angle between legs - α 60° 90° 60° 90° Chain Dia. Grade (mm) 8 2.50 5.25 4.25 3.50 2.50 6.50 3.75 6.50 5.25 3.75 10 4.00 6.80 5.60 4.00 10.40 8.40 6.00 10.40 8.40 6.00 13 6.70 11.39 9.38 6.70 17.42 14.07 10.05 17.42 14.07 10.05 16 10.00 17.00 14.00 10.00 26.00 21.00 15.00 26.00 21.00 15.00 1.0 1.7 1.4 2.6 2.1 2.1 1.0 1.5 2.6 1.5

Grade 100 - Alloy slings cannot be used at temperatures exceeding 200°C.

1 LEG SLING

2 LEG SLING





3 LEG SLING



4 LEG SLING



Assembled with chain from:





