




PLATE GRABS

A range of heavy duty steel plate grabs designed for lifting plate steel in industrial applications. Lift, lower and position with complete safety.



VERTICAL

- Vitalift Vertical Plate Grabs are suitable for the vertical lifting of plate steel up to 50mm thick
- Strong welded construction
- Spring-loaded mechanism ensures a positive initial clamping force
- Serrated grab teeth
- Spares available on request

Working Load Limit (Kg)	Jaw Opening (mm)	Eye Diameter (mm)	Net Weight (Kg)
1000	0 - 18	84	6
2000	0 - 28	78	16
3000	0 - 30	75	16
5000	5 - 50	86 x 129	39

Working Load Limit Per Pair (Kg)	Jaw Opening (mm)	Eye Diameter (mm)	Net Weight Per Pair (Kg)
1000	0 - 60	29 x 46	20
3000	0 - 100	45 x 68	43
6000	0 - 100	45 x 68	52
10000	50 - 150	60 x 68	93



HORIZONTAL

- Vitalift Horizontal Plate Grabs are suitable for secure lifting of plate steel up to 150mm thick in a horizontal position
- Grabs have an enlarged jaw opening
- Serrated grab teeth
- Used in pairs
- Spares available on request



UNIVERSAL

- Vitalift Universal Plate Grabs are suitable for secure bi-directional lifting of plate steel up to 50mm thick
- Articulated lifting shackle
- Spring-loaded mechanism ensures a positive initial clamping force
- Serrated grab teeth
- Spares available on request

Working Load Limit (Kg)	Jaw Opening (mm)	Eye Diameter (mm)	Net Weight (Kg)
1000	0 - 18	69	7.4
2000	0 - 28	72	18
3000	0 - 30	74	18
5000	0 - 50	79	44